

## Thermal Printer Specifications

|                     |                     |  |
|---------------------|---------------------|--|
| Printing            | Print method        | Direct thermal line  |
|                     | Print width         | 48mm   |
|                     | Dot density         | 384dot/line  |
|                     | Print speed         | 60mm/s   |
|                     | Interface           | Serial/USB/Parallel  |
|                     | Paper diameter      | 65mm   |
|                     | Line space          | 3.75mm(can be adjustable)  |
|                     | Character Size      | ANK Font Font A: 12x24dots Font B: 9x17dots<br>Simplified/Traditional Chinese Character: 24x24dots   |
| Barcode             | Code page           | PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/<br>Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/<br>Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/<br>PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/<br>(Vietnam)/(Thai) |
|                     | Barcode mode        | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)<br>CODE39/ITF/CODABAR/CODE93/CODE128   |
|                     | Fonts               | GB2312   |
| Buffer              | Data                | 4K bytes   |
|                     | NV Flash            | 60K bytes  |
| Power               | Cashdrawer out      | DC 12V/1A  |
|                     | Power supply        | AC 110V/220V, 50~60Hz DC 8.5V/3A   |
| Physical properties | Weight              | 0.83kg   |
|                     | Dimension           | 125x198x99mm   |
| Environment         | Work environment    | Temperature: 0~45°C, Humidity: 10~80%  |
|                     | Storage environment | Temperature: -10~60°C, Humidity: 10~90%  |
| Auto Cutter         | Reliability         | 50km   |