



Instruction:
 1.Type:Film to Glass
 2.Operating Voltage: $\leq 10V$
 3.Response Time: $\leq 10ms$
 4.Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
 5.Operation Temperature/Humidity : $-10^{\circ}C \sim +60^{\circ}C / 20\% \sim 95\%$
 6.Hitting Life: $>1,000,000$ Times ,250gf Force;
 7.writing Life: $>100,000$ Times 250gf Force;
 8.Connect Material:FPC

9.Film Thickness:0.188mm
 10.Glass Thickness:1.1mm
 11.Light transmission: $\geq 78\%$
 12.Force:100g or more
 13.Linearity: $\leq 1.5\%$
 14.Insulation: $\geq 20M \Omega$
 15.Resistance: Y: $180 \Omega \sim 330 \Omega$;
 X: $510 \Omega \sim 900 \Omega$;
 16.Surface Hardness $\geq 3H$ (pencil)

Touch-Pane-VTW4070E2

REVISIONS					
SCALE	1:1	MATERIAL	F/A	Version	1.0
UNIT	mm	TOLERANCE	± 0.05	NO.	1 of 1
DESIGN	Luoy	DATE	20100702	深圳市维拓光技术有限公司 Victor-touch Technology Co.,LTD.	
CHECK	Peter • LI	DATE	20100702		
RELEASE	Victor	DATE	20100702		